Energy Efficiency Design Summary (Part 9 Residential)

For use by Principal Authority					
Application No:			Model/Certification Number		
A. Project Information					
Building number, street name				Unit number	Lot/Con
Municipality		ostal code	Reg. Plan number / other des	scription	
Wallerpancy	'	ostar code	reg. Flammamber / other des	Scription	
B. Compliance Option					
☐ SB-12 Prescriptive [SB-12 - 2.1.1.]		Table:	Package: A B C D E F G H I J K L M (circle one)		
☐ SB-12 Performance* [SB-12 - 2.1.2.]		* Attach e	h energy performance calculations using an approved software		
☐ Energy Star®* [SB-12 - 2.1.3.]		* Attach E	* Attach Builder Option Package form		
☐ EnerGuide 80® *		* House r	House must be evaluated by NRCan advisor and meet a rating of 80		
C. Project Design Condi	tions	-			
Climatic Zone (SB-1):		pment Efficiend	y Space Heating Fuel	Source	
□ Zone 1 (< 5000 degree days)	□ ≥ 90% AFU		□ Gas	□ Propane	□ Solid Fuel
□ Zone 2 (≥ 5000 degree days) □ ≥ 78% < 90% A		% AFUE	□ Oil	□ Electric	□ Earth Energy
Windows+Skylights &Glass Doors		Other Building Conditions			
Gross Wall Area = m ² Gross Window+ Area = m ²	% Windows+		□ ICF Basement	□ Walkout Baseme	nt □ Log/Post&Beam
			□ ICF Above Grade		
D. Building Specification					
Building Component RSI / F Thermal Insulation		SI / R values	Building Component Windows & Doors ¹		Efficiency Ratings
				ss Doors	
Ceiling with Attic Space			Windows/Sliding Glas	ss Doors	
Ceiling with Attic Space Ceiling without Attic Space			Windows/Sliding Glas Skylights	ss Doors	
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor			Windows/Sliding Glass Skylights Mechanicals		
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade			Windows/Sliding Glass Skylights Mechanicals Space Heating Equip	J. ²	
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls			Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE%	J. ²	
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade)			Windows/Sliding Glass Skylights Mechanicals Space Heating Equip	J. ²	
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade)	,		Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/	% at 0°C)	ombined quater used
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he	eated)	[complete applica	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indice	6 at 0°C) m².K, or ER rating ate if condensing type c	
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V	eated)	[complete applica	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indice	6 at 0°C) m².K, or ER rating ate if condensing type c	
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance:	verification	<u> </u>	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indicate sections if SB-12 Performance	m ² .K, or ER rating ate if condensing type cance, Energy Star or En	erGuide80 options used]
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance: The annual energy consumptic The annual energy consumption	Verification on using Subson of this house	section 2.1.1. S se as designed	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indices Dele sections if SB-12 Performations B-12 Package isGj	m ² .K, or ER rating ate if condensing type cance, Energy Star or En	
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance: The annual energy consumption	Verification on using Subson of this house	section 2.1.1. S se as designed	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indices Dele sections if SB-12 Performations B-12 Package isGj	m ² .K, or ER rating ate if condensing type cance, Energy Star or En	erGuide80 options used]
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance: The annual energy consumptic The annual energy consumption	Verification on using Subson of this house the annual en	section 2.1.1. S se as designed nergy use of th	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indice sections if SB-12 Performations B-12 Package	o. ² 6 at 0°C) m ² .K, or ER rating ate if condensing type cance, Energy Star or En	erGuide80 options used]
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance: The annual energy consumptic The annual energy consumptic The software used to simulate	Verification on using Subson of this house the annual end using an air	section 2.1.1. See as designed as designed bergy use of the leakage of	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indice tole sections if SB-12 Performance B-12 Package is Gj building is: air changes per hou	o. ² 6 at 0°C)	erGuide80 options used]
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance: The annual energy consumption The annual energy consumption The software used to simulate The building is being designed Energy Star. Submit the BOP 1	Verification on using Subson of this house the annual end using an air form with Ene	section 2.1.1. See as designed as designed bergy use of the leakage of	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indice to sections if SB-12 Performations B-12 Package isGj e building is: air changes per housertification on completions	o.2 6 at 0°C) 6	erGuide80 options used]
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance: The annual energy consumption The software used to simulate The building is being designed	Verification on using Subson of this house the annual end using an air form with Ene	section 2.1.1. See as designed as designed bergy use of the leakage of	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indice tole sections if SB-12 Performance B-12 Package is Gj building is: air changes per hou	o.2 6 at 0°C) 6	erGuide80 options used]
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance: The annual energy consumption The annual energy consumption The software used to simulate The building is being designed Energy Star. Submit the BOP 1	Verification on using Subson of this house the annual end using an air form with Ene	section 2.1.1. See as designed as designed bergy use of the leakage of	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indice to sections if SB-12 Performations B-12 Package isGj e building is: air changes per housertification on completions	o.2 6 at 0°C) 6	erGuide80 options used]
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance: The annual energy consumption The annual energy consumption The software used to simulate The building is being designed Energy Star. Submit the BOP 1	Verification on using Subson of this house the annual end using an air form with Ene	section 2.1.1. See as designed as designed bergy use of the leakage of	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indice to sections if SB-12 Performations B-12 Package isGj e building is: air changes per housertification on completions	o.2 6 at 0°C) 6	erGuide80 options used]
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance: The annual energy consumption The annual energy consumption The software used to simulate The building is being designed Energy Star. Submit the BOP 1	Verification on using Subson of this house the annual end using an air form with Ene	section 2.1.1. See as designed hergy use of the leakage of	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indict ole sections if SB-12 Performations B-12 Package is Gj e building is: air changes per houe ertification on completion	m ² .K, or ER rating ate if condensing type cance, Energy Star or En is(ur @50Pa. on. Licence #:	erGuide80 options used] Gj (1 Gj =1000Mj)
Ceiling with Attic Space Ceiling without Attic Space Exposed Floor Walls Above Grade Basement Walls Slab (all >600mm below grade) Slab (edge only ≤600mm below grade, or he E. Performance Design V SB-12 Performance: The annual energy consumptic The annual energy consumptic The software used to simulate The building is being designed Energy Star. Submit the BOP the Energy Star and EnerGuide80 Evaluator/Advisor/Rater Name:	Verification on using Subson of this house the annual end using an air form with Ene	section 2.1.1. See as designed hergy use of the leakage of	Windows/Sliding Glass Skylights Mechanicals Space Heating Equip HRV Efficiency (SRE% DHW Heater (EF) NOTES 1. Provide U-Value in W/ 2. Provide AFUE or indict ole sections if SB-12 Performations B-12 Package is Gj e building is: air changes per houe ertification on completion	m ² .K, or ER rating ate if condensing type cance, Energy Star or En is(ur @50Pa. on. Licence #:	erGuide80 options used] Gj (1 Gj =1000Mj)

Form authorized by OHBA, OBOA, LMCBO. April 23, 2012

Guide to the Energy Efficiency Design Summary Form

The *Energy Efficiency Design Summary* form summarizes the compliance path used by a house designer to comply with energy efficiency requirements of the Ontario Building Code. This form must accompany the building permit application. The information on this form MUST reflect the drawings and specifications being submitted, or the building permit may be refused. Refer to Supplementary Standard SB-12 for details about building code compliance requirements. Further information about energy efficiency requirements for new buildings is available from the provincial building code website at www.mah.gov.on.ca, or the municipal building department.

Beginning January 1, 2012, a house designer must use one of four energy efficiency compliance options in the building code:

- 1. Comply with the SB-12 Prescriptive design tables,
- 2. Use the <u>SB-12 Performance</u> compliance method, and model the design against the prescriptive standards,
- 3. Design to Energy Star standards, or
- 4. Evaluate the design according to EnerGuide technical procedures and achieve a rating of 80 or more.

COMPLETING THE FORM

B. Compliance Options

Indicate the compliance option being used.

- <u>SB-12 Prescriptive</u> requires that the building conforms to a package of thermal insulation, window and mechanical system efficiency requirements set out in Subsection 2.1.1. of SB-12. Energy efficiency design modeling and testing of the building is not required under this option.
- <u>SB-12 Performance</u> refers to the alternative method of compliance set out in Subsection 2.1.2. of SB-12.
 Using this approach the designer must use recognized energy simulation software (such as HOT2000 V9.34c1.2 or newer), and submit documents which show that the annual energy use of the building is equal to a prescriptive package.
- <u>Energy Star</u> houses must be designed to *Energy Star* requirements and be labelled on completion by Enerquality or other agency. The *Energy Star* BOP form must be submitted with the permit documents.
- <u>EnerGuide80</u> houses are validated by NRCan authorized energy advisors and must achieve a rating of 80 or more when evaluated in accordance with EnerGuide administrative and technical procedures.

C. Project Design Conditions

Climatic Zone: The number of degree days for Ontario cities is contained in Supplementary Standard SB-1 Windows, Skylights and Glass Doors: If the ratio of the total gross area of windows, sidelights, skylights and glass doors to the total gross area of walls is more than 17%, higher efficiency glazing is required. If the ratio is more than 22% the <u>SB-12 Prescriptive</u> option may not be used. The total area is the sum of all the structural rough openings. Some exceptions apply. Refer to 2.1.1.1. of SB-12 for further details.

Fuel Source and Heating Equipment Efficiency: The fuel source and efficiency of the proposed heating equipment must be specified in order to determine which <u>SB-12 Prescriptive</u> compliance package table applies. Other Building Conditions: These construction conditions affect <u>SB-12 Prescriptive</u> compliance requirements.

D. Building Specifications

Thermal Insulation: Indicate the RSI or R-value being proposed where they apply to the house design. Under the <u>SB-12 Prescriptive</u> option, RSI 3.52 wall insulation is permitted in certain conditions where other design elements meet higher standards. Refer to SB-12 for further details.

E. Performance Design Summary

This section is not required to be completed if the SB-12 Prescriptive option is being used.

BUILDING CODE REQUIREMENTS FOR AIRTIGHTNESS IN NEW HOUSES

All houses must comply with increased air barrier requirements in the building code. Notice of air barrier completion must be provided and an inspection conducted prior to it being covered. The building code requires that a blower door test be conducted to verify the air tightness of the house during construction if the <u>SB-12</u> <u>Performance</u> option is used and an air tightness of less than 2.5 ACH @ 50 Pa in the case of detached houses, or 3.0 ACH @ 50 Pa in the case of attached houses is necessary to meet the required energy efficiency standard. A blower door test must also be conducted if the <u>EnerGuide 80</u> option is used.

ENERGY EFFICIENCY LABELING FOR NEW HOUSES

Energy Star and EnerGuide issue labels for new homes constructed under their energy efficiency programs. The building code does not regulate new home labelling.